

## Technical Data

Product: SCREWLINE SP 630  
Part-No.: 117008

Inlet/Outlet connection:	EN 1092-2 - PN 6 - DN 100 EN 1092-2 - PN 16 - DN 100 ISO 1609-1986 (E)-100 (DN 100 ISO-K) ASME B 16.5 NPS4 class 150	
Pumping speed at 50 Hz:	630 m <sup>3</sup> /h	371 cfm
Pumping speed at 60 Hz:	630 m <sup>3</sup> /h	371 cfm
Ultimate partial pressure without gas ballast		
at 50 Hz:	≤ 1.0 x 10 <sup>-2</sup> mbar	≤ 7.5 x 10 <sup>-3</sup> Torr
at 60 Hz:	≤ 1.0 x 10 <sup>-2</sup> mbar	≤ 7.5 x 10 <sup>-3</sup> Torr
Ultimate total pressure with gas ballast		
at 50 Hz:	≤ 1.0 x 10 <sup>-1</sup> mbar	≤ 7.5 x 10 <sup>-2</sup> Torr
at 60 Hz:	≤ 1.0 x 10 <sup>-1</sup> mbar	≤ 7.5 x 10 <sup>-2</sup> Torr
Water vapor tolerance at 50 Hz:	40.0 mbar	30.0 Torr
Water vapor tolerance at 60 Hz:	40.0 mbar	30.0 Torr
Water vapor capacity at 50 Hz:	14.0 g/h	
Water vapor capacity at 60 Hz:	14.0 g/h	
Operating fluid gear box:	LEYBONOL LVO 210	
Operating fluid capacity:	15.0 l	15.9 qt
Noise level to DIN 45 635 without gas ballast		
at 50 Hz:	73 dB(A)	
at 60 Hz:	75 dB(A)	
Mains connection:	3-ph, 200/400/690 V, 60 Hz	
Motor rating at 50 Hz:	15.0 kW	20.0 HP
Motor rating at 60 Hz:	15.0 kW	20.0 HP
Rotation speed at 50 Hz:	2.930 min <sup>-1</sup>	2.930 rpm
Rotation speed at 60 Hz:	3.530 min <sup>-1</sup>	3.530 rpm
Motor protection rating:	IP 55	
Admissible ambient temperature:	+12 to +40°C	+54 to +104°F
Dimensions:	see dimension sheet	
Weight:	≈ 530 kg	≈ 1.166 lbs

Technical data are subject to change