

## Technical Data

Product: MAG W 1600 iPL Booster

Part No.: 411600V0704

Inlet connection:	DN 250 ISO-F	
Outlet connection:	DN 40 ISO-KF	
Purge gas / venting connection:	DN 16 ISO-KF (clamp shoe)	
Pumping speed		
N <sub>2</sub> - Nitrogen:	1600 l/s	
Ar - Argon:	1470 l/s	
He - Helium:	1770 l/s	
H <sub>2</sub> - Hydrogen:	1570 l/s	
Gas throughput		
N <sub>2</sub> - Nitrogen: (continuous operation)	30.0 mbar x l/s	
N <sub>2</sub> - Nitrogen: (temporary)	60.0 mbar x l/s	
Ar - Argon: (continuous operation)	20.0 mbar x l/s	
Ar - Argon: (temporary)	30.0 mbar x l/s	
Compression ratio		
N <sub>2</sub> - Nitrogen:	$> 1.0 \times 10^7$	
Ar - Argon:	$> 1.0 \times 10^7$	
He - Helium: (at 1 sccm)	$6.0 \times 10^4$	
H <sub>2</sub> - Hydrogen: (at 1 sccm)	$1.0 \times 10^3$	
Ultimate pressure:	$< 1.0 \times 10^{-8}$ mbar	$< 7.5 \times 10^{-9}$ Torr
Max. foreline pressure for N <sub>2</sub> :	1.0 mbar	0.75 Torr
Max. foreline pressure for Ar:	1.0 mbar	0.75 Torr
Nominal rotation speed:	33000 min <sup>-1</sup>	33000 rpm
Run -up time:	< 7 min	
Mains connection:	200-240 V, 50/60 Hz	
Max. power consumption:	750 W	
Power consumption at ultimate pressure:	150 W	
Interfaces		
Control Slot:	ProfiBus	
Service Slot:	RS232	
Protection rating:	IP 54	

## Technical Data

Product: MAG W 1600 iPL Booster  
Part No.: 411600V0704

Admissible ambient temperature:	+10 to +45°C	+50 to +113°F
Cooling:	Water	
Cooling water connection:	G 1/8", Inside thread	
Cooling water consumption:	> 60 l/h	
Max. Permissible cooling water pressure:	6 bar	
Permissible cooling water temperature:	+10 to +35°C	+50 to +95°F
Dimensions:	see dimension sheet	
Weight:	≈ 45.0 kg	

Technical data are subject to change