

Technical Data

Product: MAG W 2200 iP

Part No.: 412200V0504

Inlet connection:	DN 250 ISO-F
Outlet connection:	DN 40 ISO-KF
Purge gas / venting connection:	DN 16 ISO-KF (clamp shoe)

Pumping speed	
N ₂ - Nitrogen:	2100 l/s
Ar - Argon:	1900 l/s
He - Helium:	2050 l/s
H ₂ - Hydrogen:	1750 l/s

Gas throughput	
N ₂ - Nitrogen: (continuous operation)	20.0 mbar x l/s
N ₂ - Nitrogen: (temporary)	30.0 mbar x l/s
Ar - Argon: (continuous operation)	15.0 mbar x l/s
Ar - Argon: (temporary)	20.0 mbar x l/s

Compression ratio	
N ₂ - Nitrogen:	$> 1.0 \times 10^8$
Ar - Argon:	$> 1.0 \times 10^8$
He - Helium: (at 1 sccm)	5.0×10^4
H ₂ - Hydrogen: (at 1 sccm)	5.0×10^3

Ultimate pressure:	$< 1.0 \times 10^{-8}$ mbar	$< 7.5 \times 10^{-9}$ Torr
Max. foreline pressure for N ₂ :	2.5 mbar	1.9 Torr
Max. foreline pressure for Ar:	2.5 mbar	1.9 Torr
Nominal rotation speed:	30600 min ⁻¹	30600 rpm
Run -up time:	< 7 min	
Mains connection:	200-240 V, 50/60 Hz	
Max. power consumption:	750 W	
Power consumption at ultimate pressure:	150 W	

Interfaces	
Control Slot:	Profibus
Service Slot:	RS232

Protection rating:	IP 54
--------------------	-------

Technical Data

Product: MAG W 2200 iP
Part No.: 412200V0504

Admissible ambient temperature:	+10 to +45°C	+50 to +113°F
Cooling:	Water	
Cooling water connection:	G 1/8", Inside thread	
Cooling water consumption:	> 60 l/h	
Max. Permissible cooling water pressure:	6 bar	
Permissible cooling water temperature:	+10 to +35°C	+50 to +95°F
Dimensions:	see dimension sheet	
Weight:	≈ 50.0 kg	

Technical data are subject to change